

Stainless Steel Wire Cloth Coarse and Medium (Market Grade)

Mesh	Wire dia. in inches	Wire dia. in mm	Opening in inches	Opening in mm / μ	Open Area in %	Weight kg/sqm
2	0.063	1.60	0.4370	11.2 mm	77	2.56
3	0.054	1.40	0.2790	7.10	69.4	2.96
4	0.047	1.25	0.2030	5.00	64	3.21
5	0.041	1.00	0.1590	4.00	64	2.58
6	0.035	0.90	0.1320	3.35	62.1	2.45
8	0.028	0.71	0.0970	2.50	60	2.01
10	0.025	0.63	0.0750	2.00	57.6	1.95
12	0.023	0.63	0.0600	1.50	49.6	2.39
14	0.020	0.50	0.0510	1.32	52.6	1.77
16	0.018	0.45	0.0445	1.12	51	1.66
18	0.017	0.40	0.0386	1.00	51	1.46
20	0.0160	0.40	0.0340	850 μ	46.2	1.65
24	0.0140	0.36	0.0277	710	44.4	1.57
30	0.0120	0.28	0.0213	560	44.4	1.20
35	0.0110	0.28	0.0176	450	38	1.38
40	0.0100	0.25	0.0150	400	38	1.23
50	0.0090	0.22	0.0110	280	31	1.24
60	0.0075	0.18	0.0092	224	31	1.03
80	0.0055	0.14	0.0070	180	31	0.79

All technical datas are subject to revision!